

## ALTO HOUSE HEAT PUMP SPECIFICATION LIST

Model (R410A)		APX-H012	APX-H028	APX-H060	APX-H085
Hot water (L/hr)	60 °C	57	113	246	355
	50°C	66	132	290	442
Heating Capacity (w)		2500	5000	10000	15000
Power Consumption (w)		665	1260	2535	3460
Amperage (Amp)		3.22	5.85	5.40	6.58
Noise (dB(A))		50	53	55	58
Outdoor unit weight		25	43	75	96
Outdoor unit dimension		600 x 502 x 232	772 x 540 x 254	880 x 780 x 360	930 x 1800 x390
Power Supply		230V/1ph/50Hz	230V/1ph/50Hz	380V/3ph/50Hz	380V/3ph/50Hz
Connecting copper pipe		IN3/8" OUT3/8"	IN3/8" OUT3/8"	IN3/8" OUT5/8"	IN3/8" OUT5/8"
Tank model		100L\150L\200L	100L\150L\200L\300L	200L\300L\400L	200L\300L\400L

Model (R407C)		APX-H012	APX-H028	APX-H060	APX-H085
Hot water (L/hr)	60 °C	57	113	246	355
	50°C	66	132	290	442
Heating Capacity (w)		2500	5000	10000	15000
Power Consumption (w)		675	1270	2550	3480
Amperage (Amp)		3.27	5.93	5.45	6.62
Noise (dB(A))		50	53	55	58
Outdoor unit weight		25	43	75	96
Outdoor unit dimension		600 x 502 x 232	772 x 540 x 254	880 x 780 x 360	930 x 1800 x390
Power Supply		230V/1ph/50Hz	230V/1ph/50Hz	380V/3ph/50Hz	380V/3ph/50Hz
Connecting copper pipe		IN3/8" OUT3/8"	IN3/8" OUT3/8"	IN3/8" OUT5/8"	IN3/8" OUT5/8"
Tank model		100L\150L\200L	100L\150L\200L\300L	200L\300L\400L	200L\300L\400L